

TANYL® N

OAK ELLAGIC TANNIN, FOR OE-NOLOGICAL USE.

COMPOSITION

TANYL® N is an ellagic tannin made from oak wood. It contains a high percentage of tannins extracted from oak which gives **TANYL® N** a large number of oenological properties and qualities.

APPLICATIONS

TANYL® N is intented for white, rosé and red wines ageing. It is perfectly suited to standard quality wines. Its high concentration of ellagitannins, allows to:

- Recreate a rich elllagic tannins environment in used barrels identical to that of new barrels.
- Protect wine against oxydation
- Stabilize red wine color

DIRECTIONS FOR USE

For direct addition, slowly add the tannin by sprinkling it while mixing. As part of a liquid addition, dissolve one part of **TANYL® N** in 10 parts of water and add the solution to the wine while mixing continuously.

DOSAGE

- White wines: 5 to 15 grams per hectoliter
- Red wines: 10 to 20 grams per hectoliter

We recommend that you carry out laboratory tests beforehand in order to define and adjust the dose that will meet your oenological objectives.

It is specified in the Oenological Codex that tannins "must not change the olfactory properties and the colour of wine". The dosage rates will therefore vary in function of the wine matrix, and shall be determined after trials.

Qualified for the elaboration of products for direct human consumption in the field of the regulated use in oenology. In conformity with (UE) 2019/934.

In accordance with oenological codex..





TANYL® N

OAK ELLAGIC TANNIN, FOR OENOLOGICAL USE.

PHYSICAL CHARACTERISTICS

Origin Oak wood (Que	ercus sp.)	Odor
Aspect Fine powder (a	tomized)	Flavoi
Granulometryless than 130µ	(at 95%)	Solub
Color	rk brown	

Odor	Typical of oak wood
Flavor	Astringent (presence of tannins)
Solubility	Water or hydroalcoholic medium

EXTRACTION CHARACTERISTICS

Classification	Natural plant extract
Solvents used	Water
Manufacturing adjuvants	None

Staining adjuvants	None
Conservatives	None

ANALYTICAL CHARACTERISTICS

Total polyphenol content > =	65	%
Loss on drying < =	= 10	%
Insoluble substances <	= 2	%
Ash < :	= 4	%

Arsenic	< 3	ppm
Iron	50	ppm
Mercury	< 1	ppm
Lead	< 5	maa

STORAGE

- Store above ground level in the original packaging, away from light and moisture, at moderate temperatures, in a dry area
- Do not inhale or absorb. In case of a problem, refer to the Safety Data Sheet
- DMD (Optimal date of use) : 3 years

PACKAGING

■ kraft drums of 25 kg

Contact us for a different packaging